

# NEW TRIA® UNIVERSAL

**LED module, 2500/3000/4000 K, 60°, PHASE, black**

Discover the new generation of our NEW TRIA® recessed ceiling light and configure an individual lighting experience. A modular element is the multi-wattage LED MODULE, which is variably adjustable in terms of output (4.4 W/5.5 W/7.3 W/8.6 W) and light intensity (540 lm/600 lm/600 lm). The CCT switch, which allows easy selection between 2500 K, 3000 K and 4000 K, also provides even more lighting design options. The LED MODULE is available with different beam angles (38°/60°) as a phase variant. The robust design and excellent colour reproduction index CRI >90 ensure exceptional quality. In addition, the NEW TRIA® UNIVERSAL LED MODULE impresses with its service life of L80B10@50,000h.

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007432 |
| **IP Code** | IP20 |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 100-180 mA |
| **Safety class** | II |
| **Wattage** | 8.6 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 35 °C |
| **Number of luminaires at LS B16A** | 128 |
| **Number of luminaires at LS C16A** | 212 |
| **Level of inrush current** | 10 A |
| **Duration of inrush current** | 100 µs |
| **Lumen** | 540/600/600 lm |
| **Colour temperature** | 2500/3000/4000 Kelvin |
| **Beam angle** | 60 ° |
| **Color** | black |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 3.3 cm |
| **Diameter** | 5 cm |

| | |
|---|---|
| 1807470 |  |

## Accessories

| | |
|---|---|
| 1007630 | NEW TRIA® 75 XL , ceiling installation ring, D: 11 H: 2.6 cm, IP20, white |
| 1007349 | NEW TRIA® 75 , ceiling installation ring, L: 9 W: 9 H: 2.6 cm, IP 20, white |
| 1007337 | NEW TRIA® 68 , ceiling installation ring, D: 8.3 H: 3.55 cm, IP 65, incl. glass, white |
| 1007634 | NEW TRIA® 75 XL , ceiling installation ring, L: 11 W: 11 H: 2.6 cm, white |
| 1007453 | NEW TRIA® 68 , ceiling installation ring, recessed, D: 8.2 H: 4.4 cm, IP 20, white |
| 1007346 | NEW TRIA® 68 , ceiling installation ring, D: 8.2 H: 3.4 cm, IP 65, white |
| 1007450 | NEW TRIA® 75 , ceiling installation ring, recessed, attachment, D: 8.2 H: 4.9 cm, IP 20, white |
| 1007328 | NEW TRIA® 68 , ceiling installation ring, L: 8.2 W: 8.2 H: 2.6 cm, IP 20, white |
| 1007489 | NEW TRIA® 75 , ceiling installation ring, recessed, D: 8.2 H: 4.3 cm, IP 20, white |
| 1007348 | NEW TRIA® 68 , ceiling installation ring, L: 8.2 W: 8.2 H: 3.4 cm, IP 65, white |
| 1007333 | NEW TRIA® 68 , ceiling installation ring, D: 8.2 H: 2.6 cm, IP 20, white |
| 1007339 | NEW TRIA® 68 , ceiling installation ring, L: 8.3 W: 8.3 H: 3.55 cm, IP 65, incl. glass, white |
| 1007342 | NEW TRIA® 75 , ceiling installation ring, D: 9.3 H: 2.6 cm, IP 20, white |

| | |
|---|---|
| **Net weight** | 0.154 kg |
| **Gross weight** | 0.183 kg |
| **BIG WHITE Page** | 119 |