


NEW TRIA® 68

ceiling installation ring, recessed, D: 8.2 H: 4.4 cm, IP 20, black

Discover the new generation of our NEW TRIA® series and configure an individual lighting experience. A modular element is the square or round mounting ring, which is available as a pivoting and rotating or all-round protected IP 65 version. In the colours black, white, rose gold or brushed aluminium, it blends harmoniously into any room ambience. For easy assembly, the mounting ring, specially designed for a hole diameter of 68mm, is supplied with clip and leaf springs.



TECHNICAL DATA

Item no.	1007451
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Color	black
Height	4.4 cm
Diameter	8.2 cm
Net weight	0.08 kg
Gross weight	0.086 kg
Shape of cut-out	round
Installation diameter	6.8 cm
BIG WHITE Page	126

Accessories

1007381	NEW TRIA® , LED module, 2700K, 38°, PHASE, black
1007431	NEW TRIA® UNIVERSAL , LED module, 2500/3000/4000K, 38°, PHASE, black
1007422	NEW TRIA® , LED module, round, 1800-3000K, 60°, PHASE, black
1007384	NEW TRIA® , LED module, 3000K, 60°, PHASE, black
1007432	NEW TRIA® UNIVERSAL , LED module, 2500/3000/4000K, 60°, PHASE, black
1007383	NEW TRIA® , LED module, 3000K, 38°, PHASE, black
1007283	GU10 fitting for LED light (max. 10W) with quick installation box and strain relief
1007382	NEW TRIA® , LED module, 2700K, 60°, PHASE, black
1007421	NEW TRIA® , LED module, round, 1800-3000K, 38°, PHASE, black