






# WORKLIGHT PRO

**free-standing lamp, 100W, 4000K, Touch, black**

The new WORKLIGHT PRO stands for high performance in the workplace: the free-standing lamp is optimally designed in line with the latest DIN EN 12464:2021 standard. Its glare-free (UGR<14) luminous efficiency of 130 lm/W, a colour temperature of 4000K and improved, indirect light output offers everything you need for an ergonomic working environment. Dimmability, daylight control, a motion sensor and long lifespan (L80/B10 50,000h) also help to make the free-standing office lamp what it is: a true SLV colleague that assists with productivity.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007462 |
| **Number of different light outlets** | 2 |
| **IP Code** | IP 20 |
| **Impact resistance class** | IK 03 |
| **Impact resistance** | 0.35 Joule |
| **Assembly** | Mobile |
| **Dimmable** | Yes |
| **Dimming technology** | Touch |
| **Primary nominal voltage** | 200-240V ~50/60Hz |
| **Secondary power / voltage** | 48 V |
| **Safety class** | I |
| **Wattage** | 100 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 7 |
| **Number of luminaires at LS C16A** | 12 |
| **Level of inrush current** | 46 A |
| **Duration of inrush current** | 280 µs |
| **Stroboscopic effect (SVM)** | 0.4 |
| **Lumen** | 13000 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 75 ° |

| | |
|---|---|
| 1807475 |  |
| 1807479 |  |

| | |
|---|---|
| **Color** | black |
| **CRI** | 80 |
| **UGR ≤** | 14 |
| **LXXBXX data** | L80B10 |
| **Service life** | 50000 h |
| **Risk Group** | 0 |
| **Length** | 83.5 cm |
| **Width** | 24 cm |
| **Height** | 196 cm |
| **Net weight** | 14.1 kg |
| **Gross weight** | 15.087 kg |
| **BIG WHITE Page** | 444 |