


WATERPROOF V 1200

18/32W 830/840 IP66

Discover our new technical product range: SLVtec.With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the WATERPROOF V light, which is protected against strong jets of water thanks to protection code IP66 and is also available as a DALI version. The light colour (3000K/4000K) and light intensity can be easily changed via dip switches. The pre-installed through-wiring kit allows two lights to be connected quickly and easily. Installation is also extremely easy thanks to the removable equipment rack. Decide in favour of SLVtec today.



TECHNICAL DATA

Item no.	1007490
IP Code	IP 66
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling,Wall
Number of through-wires	50
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350/300/250 mA
Safety class	I
Wattage	32 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	52
Number of luminaires at LS C16A	83
Level of inrush current	17 A
Duration of inrush current	140 µs
Stroboscopic effect (SVM)	0.02
Lumen	3860/4130 lm
Colour temperature	3000/4000 Kelvin
Color	grey
CRI	80
LXXBXX data	L80B10

1807484	

Service life	50000 h
Risk Group	0
Length	123.6 cm
Width	8 cm
Height	7.6 cm
Net weight	1.55 kg
Gross weight	1.659 kg