
# PANEL V 600

**34W 830/840 UGR**

Discover our new technical product range: SLVtec.With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the PANEL V light, which is available as a surface-mounted, recessed and DALI version. The light colour (3000K/4000K) and light intensity (4100lm/4350lm) can be easily changed via dip switches. Thanks to the high light output of up to 120 lm/W and the UGR<19, the lights are particularly suitable for office spaces where glare-free and homogeneous illumination is important. For this purpose, the external driver enables easy installation. Decide in favour of SLVtec today.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007498 |
| **IP Code** | IP 40 / IP 54 |
| **Impact resistance** | 0.35 Joule |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling,Ceiling with Acc. |
| **Primary nominal voltage** | 220-240V ~50/60Hz |
| **Secondary power / voltage** | 900 mA |
| **Safety class** | II |
| **Wattage** | 34 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Operating efficiency (LOR)** | 1 |
| **Number of luminaires at LS B16A** | 30 |
| **Number of luminaires at LS C16A** | 51 |
| **Level of inrush current** | 30 A |
| **Duration of inrush current** | 110 µs |
| **Stroboscopic effect (SVM)** | 0.4 |
| **Lumen** | 4000/4200 lm |
| **Colour temperature** | 3000/4000 Kelvin |
| **Beam angle** | 85 ° |
| **Color** | white |
| **CRI** | 80 |

| | |
|---|---|
| 1807491 |  |

## Accessories

| | |
|---|---|
| 1007577 | PANEL V , safety rope 1500mm |
| 1007474 | PANEL 600 , assembly mounting frame |
| 1007575 | PANEL 600 , recessed mounting frame |

| | |
|---|---|
| UGR ≤ | 19 |
| LXXBXX data | L80B10 |
| Service life | 50000 h |
| Risk Group | 0 |
| Length | 59.5 cm |
| Width | 59.5 cm |
| Height | 2.8 cm |
| Net weight | 2.1 kg |
| Gross weight | 2.22 kg |
| Shape of cut-out | square |
| Installation length | 58.5 cm |
| Installation width | 58.5 cm |
| Installation depth | 8 cm |