


SURFACE V 390

10/15/20W 830/840 IP44

Discover our new technical product range: SLVtec.With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the high-quality designed SURFACE V wall-mounted light, which is optionally available with a motion sensor. The light colour (3000-K/4000K) and light intensity (1850lm/200lm) can be easily adjusted via dip switches. With a large beam angle of 120°, it homogeneously illuminates any environment, and its service life of 50,000 hours makes it ideal for long-term use. And the removable cover also makes installation easy. Decide in favour of SLVtec today.



TECHNICAL DATA

Item no.	1007516
IP Code	IP 44
Assembly	Surface
Assembly details	Ceiling,Wall
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	165/120/84 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	13
Number of luminaires at LS C16A	22
Level of inrush current	25.4 A
Duration of inrush current	200 µs
Stroboscopic effect (SVM)	0.4
Lumen	1850/2000 lm
Colour temperature	3000/4000 Kelvin
Beam angle	120 °
Color	white
CRI	80
LXXBXX data	L80B10

771797	

Service life	50000 h
Height	11.5 cm
Diameter	39 cm
Net weight	0.74 kg
Gross weight	1.34 kg