


ONE FLAT PD

pendant light, pendant length 180cm, 2700/3000K, PHASE, white

The new ONE FLAT pendant light adds another new member to the popular SLV light family that guarantees a truly elegant look. The flat ring emits a phase-dimmable, adjustable colour temperature (2700/3000K) and colour-neutral (CRI>90) light via CCT switch that is especially long-lasting at 50,000 hours. Perfect for upmarket living rooms or commercial areas. A well-rounded lighting experience.



TECHNICAL DATA

Item no.	1007856
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	600 mA
Safety class	I
Wattage	23 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	94
Number of luminaires at LS C16A	94
Level of inrush current	5 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.4
Lumen	1900/2050 lm
Colour temperature	2700/3000 Kelvin
Color	matt white
CRI	90
LXXBXX data	L80B10

2014567	

Service life	50000 h
Risk Group	1
Height	2 cm
Diameter	60 cm
Pendant length	180 cm
Net weight	3.296 kg
Gross weight	5.166 kg