


# Q-RING

**wall light, 3000K, PHASE, IP65, black**

The new Q-RING family elegantly picks up on the trend towards organic shapes. The indirect and warm white light (3000 K) illuminates façades discreetly and glare-free. Thanks to the special surface treatment, it can also be used in coastal areas.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007918 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 06 |
| **Impact resistance** | 2 Joule |
| **Assembly** | Surface |
| **Assembly details** | Wall |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Number of through-wires** | 20 |
| **Primary nominal voltage** | 220-240V ~50/60Hz |
| **Secondary power / voltage** | 240 mA |
| **Safety class** | I |
| **Wattage** | 10 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Operating efficiency (LOR)** | 0,53 |
| **Number of luminaires at LS B16A** | 96 |
| **Number of luminaires at LS C16A** | 96 |
| **Level of inrush current** | 4.1 A |
| **Duration of inrush current** | 104 µs |
| **Temperature at glass (light emission)** | 50 °C |
| **Stroboscopic effect (SVM)** | 0.03 |

| | |
|---|---|
| |  |

| | |
|---|---|
| **Lumen** | 950 lm |
| **Colour temperature** | 3000 Kelvin |
| **Color** | black |
| **CRI** | 80 |
| **LXXBXX data** | L80B50 |
| **Service life** | 30000 h |
| **Depth** | 11 cm |
| **Diameter** | 27 cm |
| **Net weight** | 1.04 kg |
| **Gross weight** | 1.113 kg |