

NEW TRIA® | DL, DOUBLE LED-MODUL, PHASE

NEW TRIA® 155, DOUBLE LED module, 2700 K, 38°, PHASE, black

Discover the new generation of our NEW TRIA® recessed ceiling lights with even more possibilities for an individual lighting experience. The DOUBLE LED module makes the design options even more diverse: the set includes two premium LED light sources with CRI >90 and 6 watts of power each, whose warm white light can not only be swivelled through 38°, but can also be phase dimmed using the driver supplied. You also have the choice between 2700 K and 3000 K. Combine the DOUBLE LED module with a NEW TRIA® 155 recessed ceiling ring of your choice.

Light source

869193	A F G

Accessories

1008007	NEW TRIA® 155, ceiling installation ring, L: 17 W: 9 H: 4 cm, two-lamp, IP 20, black
1008008	NEW TRIA® 155, ceiling installation ring, L: 17 W: 9 H: 4 cm, two-lamp, IP 20, white
1008009	NEW TRIA® 155, ceiling installation ring, L: 17 W: 9 H: 4 cm, two-lamp, IP 20, aluminium

Item no.	1008005
Lamps included	No
Number of different light outlets	2
IP Code	IP20
Dimmable	true
Dimming technology	Leading edgetrailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	85.0
Number of luminaires at LS C16A	144.0
Level of inrush current	2 A
Duration of inrush current	80 µs
Beam angle	38°
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	4 cm
Diameter	5 cm
Net weight	0.23 kg
Gross weight	0.27 kg
BIG WHITE Page	83