




CYFT WAVE

wall- and ceiling-mounted light, 2700/3000/4000 K, 6.5 W, PHASE, black / clear

Illuminate rooms with the CYFT WAVE. The LED wall and ceiling light with transparent glass shade and wave cut creates aesthetic accents, while at the same time providing optimum protection against moisture with IP65. This makes it ideal for bathrooms or indoor and outdoor corridors. With a high CRI >90 and the CCT switch, you can switch between warm 2700 K, natural 3000 K or the cooler 4000 K to achieve the perfect mood. Complete the look with optional decorative rings in six colours. Discover CYFT WAVE: stylish lighting that adapts to your wishes.



TECHNICAL DATA

Item no.	1008024
IP Code	IP65
Impact resistance class	IK 05
Impact resistance	0.7 Joule
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	200
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	6.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	224
Number of luminaires at LS C16A	266
Level of inrush current	5 A
Duration of inrush current	100 µs
Lumen	240/260/280 lm
Colour temperature	2700/3000/4000 Kelvin
Color	black/transparent
CRI	90
UGR ≤	22

1807506	

Accessories

1008026	Decorative ring , for CYFT, matte nickel
1007610	CYFT , decorative ring, brass
1008943	
1008025	Decorative ring , for CYFT, bronze
1007609	CYFT , decorative ring, chrome
1007611	CYFT , decorative ring, white

Service life	50000 h
Risk Group	0
Height	7.9 cm
Diameter	13.2 cm
Net weight	1.36 kg
Gross weight	1.68 kg
BIG WHITE Page	439