




RASTERLYSWL

wall-mounted light, rectangular, 2700/3000 K, 14 W, PHASE, 70°, anthracite

The RASTERLYS series combines modern design with high functionality. Whether mounted as a single light or in a row - the wall and bollard lights not only provide effective illumination, but also make an aesthetic statement on façades, entrances, terraces or in outdoor areas of catering establishments.with warm white light (2,700 K / 3,000 K via CCT switch), they create atmospheric accents in outdoor areas. Thanks to its IP65 and salt air-resistant surface, RASTERLYS is particularly robust and durable. The Triac dimming function and the loop-in/loop-out connection enable flexible and efficient installation.



TECHNICAL DATA

Item no.	1008384
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	160
Number of luminaires at LS C16A	160
Level of inrush current	5 A
Duration of inrush current	100 µs
Temperature at glass (light emission)	55 °C
Lumen	350 / 400 lm

2166513	

Colour temperature	2700/3000 Kelvin
Beam angle	70 °
Color	anthracite
CRI	80
Service life	50000 h
Width	12 cm
Height	21 cm
Depth	7.6 cm
Net weight	1.3 kg
Gross weight	1.5 kg
BIG WHITE Page	853