




# RASTERLYSPOLE 70

**free-standing lamp, 2700/3000 K, IP65, rectangular, anthracite**

The RASTERLYS series combines modern design with high functionality. Whether mounted as a single light or in a row - the wall and bollard lights not only provide effective illumination, but also make an aesthetic statement on façades, entrances, terraces or in outdoor areas of catering establishments.with warm white light (2,700 K / 3,000 K via CCT switch), they create atmospheric accents in outdoor areas. Thanks to its IP65 and salt air-resistant surface, RASTERLYS is particularly robust and durable. The Triac dimming function and the loop-in/loop-out connection enable flexible and efficient installation.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008385 |
| **Number of different light outlets** | 2 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 06 |
| **Impact resistance** | 1 Joule |
| **Assembly** | Surface |
| **Assembly details** | Ground |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Primary nominal voltage** | 220-240V ~0/50/60 Hz |
| **Secondary power / voltage** | 700 mA |
| **Safety class** | I |
| **Wattage** | 27 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 28 |
| **Number of luminaires at LS C16A** | 59 |
| **Level of inrush current** | 10 A |
| **Duration of inrush current** | 300 µs |
| **Temperature at glass (light emission)** | 60 °C |
| **Lumen** | 700 / 750 lm |
| **Colour temperature** | 2700/3000 Kelvin |

| | |
|---|---|
| 2166513 |  |

## Accessories

| | |
|---|---|
| 228726 | Y-CONNECTION BOX , black, IP68 |
| 228730 | CONNECTION BOX , 3-pin, IP68 |

| | |
|---|---|
| **Beam angle** | 70 ° |
| **Color** | anthracite |
| **CRI** | 80 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 17 cm |
| **Width** | 10 cm |
| **Height** | 70.2 cm |
| **Net weight** | 2.7 kg |
| **Gross weight** | 3.3 kg |
| **BIG WHITE Page** | 731 |