




# SYNA WIDE

**ground spike light, 2200 K, 115°, IP65, square, black**

The SYNA WIDE ground spike lights with IP65 protection are equipped with a 6 W LED and are available in the light colours 2200 K and 3000 K. They offer a wide 115° beam angle, ideal for illuminating bushes and facades. With a service life of 30,000 hours and a robust aluminium housing that is easy to attach using a ground spike, they are perfect for outdoor use. The connection is made via a 1.5 m cable with a Schuko plug (IP44).




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008478 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 06 |
| **Impact resistance** | 1 Joule |
| **Assembly** | Mobile |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 500 mA |
| **Safety class** | I |
| **Wattage** | 5.5 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 64 |
| **Number of luminaires at LS C16A** | 102 |
| **Level of inrush current** | 15 A |
| **Duration of inrush current** | 200 µs |
| **Temperature at glass (light emission)** | 60 °C |
| **Lumen** | 500 lm |
| **Colour temperature** | 2200 Kelvin |
| **Beam angle** | 115 ° |
| **Color** | black |
| **CRI** | 80 |

| | |
|---|---|
| 2166515 |  |

| | |
|---|---|
| **Binning** | 3.8 SDCM |
| **Service life** | 30000 h |
| **Risk Group** | 1 |
| **Width** | 7.6 cm |
| **Height** | 8.5 cm |
| **Depth** | 10.5 cm |
| **Length of earth spike** | 17.3 cm |
| **Net weight** | 0.58 kg |
| **Gross weight** | 0.65 kg |
| **BIG WHITE Page** | 804 |