


MEDO® RING 60

pendant light, pendant length 300cm, 3000/4000K, 110°, PHASE, white

The best MEDO® of all time is now also available as a pendant light in an elegant design: the MEDO® RING impresses with a longer service life and better energy efficiency of over 120 lm/W. It is available in two sizes and two colours, and can be controlled via trailing edge or DALI. The CCT switch (3000K/4000K) allows the light temperature to be selected as desired.



TECHNICAL DATA

Item no.	1008592
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	30
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	27 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	56
Number of luminaires at LS C16A	84
Level of inrush current	5 A
Duration of inrush current	300 µs
Temperature at glass (light emission)	29 °C
Lumen	3750/4000 lm
Colour temperature	3000/4000 Kelvin
Color	white
CRI	90
UGR ≤	25

Service life	50000 h
Height	7 cm
Diameter	60 cm
Pendant length	300 cm
Net weight	3.82 kg
Gross weight	5.7 kg