
PANEL C

DALI 1200 34 W 830/840 UGR

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the PANEL C luminaires, which impress with their high energy efficiency of over 130 lm/W and a long service life of L80B10-70,000 hours. They are available in three sizes, with all versions also available as DALI versions. Thanks to the glare-free light with a UGR<19, they are ideal for basic lighting in offices.



TECHNICAL DATA

Item no.	1008607
IP Code	IP20/IP54
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	850
Safety class	II
Wattage	34 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	29
Number of luminaires at LS C16A	48
Level of inrush current	14.75 A
Duration of inrush current	256 µs
Lumen	4550/4650 lm
Colour temperature	3000/4000 Kelvin
Color	white
CRI	80
UGR ≤	19

Service life	70000 h
Risk Group	0
Length	119.5 cm
Width	29.5 cm
Height	2.8 cm
Net weight	1.85 kg
Gross weight	2.35 kg
Shape of cut-out	rectangular
Installation length	117 cm
Installation width	27 cm
Installation depth	8 cm