


OCULUS

wall-mounted light, round, 2000-3000K, 15W, dim-to-warm, PHASE, 100°, dark copper

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light, every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting. In addition to the classic black and white versions, all OCULUS lights are also available in three other elegant colours. The high-quality PVD coating ensures outstanding surface properties.



TECHNICAL DATA

Item no.	1008614
Number of different light outlets	2
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	14 A
Duration of inrush current	8.5 µs
Lumen	22-550 lm
Colour temperature	2000-3000 Kelvin
Color	dark copper
CRI	90
Service life	30000 h
Risk Group	1

Height	11 cm
Depth	12.5 cm
Diameter	9 cm
Net weight	0.85 kg
Gross weight	1.03 kg