


MEDO® 40 | 40 RL, frame

MEDO® 40, recessed ceiling light, frame, 3000/4000 K, 80°, IP20, round, white

The MEDO® 40 is a round recessed ceiling luminaire designed for indoor use with an IP20 protection rating. It offers a luminous flux of 2350 to 2450 lumens at a colour temperature of 3000 or 4000 Kelvin and a beam angle of 80°. The housing is white, with a diameter of 40 cm and a height of 10 cm. The luminaire has a declared service life of 50,000 hours. It is intended for recessed ceiling installation and is particularly suitable for applications requiring uniform, glare-free general lighting. No details on control functions or special optical components are provided.



Light source

1807453	A C G

Item no.	1008631
Lamps included	No
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling,
Secondary power / voltage	500 mA
Safety class	III
Wattage	16 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Beam angle	80°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	10 cm
Diameter	40 cm
Net weight	2.15 kg
Gross weight	3.55 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	39 cm
BIG WHITE Page	89

Accessories

1008699	LED driver, 150-200mA | 21W
1008670	Strain relief, standard, for non-dimmable drivers: 1008699, 1008700, 1008701
1008671	Strain relief, through-wirable, for non-dimmable drivers: 1008699, 1008700, 1008701
1008663	LED driver 20 W, 350-500 mA, PHASE
1008667	LED driver 23 W, 100-700 mA, DALI
1008672	Strain relief, standard, for DALI-dimmable drivers: 1008666, 1008667, 1008668
1008673	Strain relief through-wirable, for DALI dimmable drivers: 1008666, 1008667, 1008668