


# MEDO® 60

**recessed ceiling light, frameless, 3000/4000K, 80°, IP20, round, white**

The best MEDO® of all time is also available as a recessed ceiling light in four different sizes, including frame or frameless. It impresses with a longer service life and subsidised energy efficiency of over 140 lm/W. The colour rendering index CRI>90 ensures true-colour and, with UGR<19, virtually glare-free light quality, making it suitable for use in offices. The CCT switch enables you to choose between 3000 K and 4000 K, letting you personalise your lighting situation. Please note that the driver and strain relief must be purchased separately.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008634 |
| **IP Code** | IP20 |
| **Assembly** | Recessed |
| **Secondary power / voltage** | 1000 mA |
| **Safety class** | III |
| **Wattage** | 33 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 45 °C |
| **Lumen** | 4600/4600 lm |
| **Colour temperature** | 3000/4000 Kelvin |
| **Color** | white |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 12.5 cm |
| **Diameter** | 60 cm |
| **Net weight** | 4.4 kg |
| **Gross weight** | 8 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 16 cm |
| **Installation diameter** | 61 cm |

## Accessories

| | |
|---|---|
| 1008669 | LED driver 53W , 650-1400mA, DALI |
| 1008701 | |
| 1006871 | NUMINOS® PROJECTOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / white |
| 1006870 | NUMINOS® PROJECTOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / black |
| 1008674 | Strain relief standard , for DALI dimmable drivers: 1008669 |
| 1008665 | LED driver 40W , 700-1050mA, PHASE |
| 1008702 | |