

LED driver 36 W

100-900 mA, DALI

This DALI and push-dim capable constant current driver with 36 W output offers an adjustable current via DIP: 150 mA, 200 mA, 250 mA, 300 mA, 350 mA, 400 mA, 450 mA, 500 mA, 550 mA, 600 mA, 650 mA, 700 mA, 800 mA, 850 mA, 900 mA. A strain relief is optionally available

TECHNICAL DATA

Item no.	1008668
IP Code	IP20
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	150-900 mA
Safety class	II
Safety class	II
Wattage	40.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	59
Number of luminaires at LS C16A	94
Level of inrush current	8.5 A
Duration of inrush current	16 µs
Color	white
Depth	0 cm
Net weight	0.107 kg
Gross weight	0.116 kg
BIG WHITE Page	1018

Accessories

1008673	Strain relief through-wirable , for DALI dimmable drivers: 1008666, 1008667, 1008668
1008672	Strain relief , standard, for DALI-dimmable drivers: 1008666, 1008667, 1008668