
GRIP! S

Ceiling-mounted light, single, PHASE, 2700K, 11W, 29°, bronze / black

GRIP! - the striking light family for sophisticated lighting design. With its distinctive knurled front ring and many new pendant, surface-mounted and recessed options, GRIP! now offers even more options for customised lighting concepts. The honeycomb louvre insert supplied as standard reduces glare and ensures optimum visual comfort. Different colours and designs blend harmoniously into living spaces, hotels or restaurants. High-quality technology with a CRI of 90, a lifetime of 50,000 hours and easy installation make GRIP! an all-round convincing choice.



TECHNICAL DATA

Item no.	1009040
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	260 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	0 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	200
Number of luminaires at LS C16A	200
Level of inrush current	5 A
Duration of inrush current	100 µs
Lumen	600 lm
Colour temperature	2700 Kelvin
Beam angle	29 °
Color	bronze/black

2093820	

Accessories

1008489	GRIP! S , decorative ring, black
1008488	GRIP! S , decorative ring, white
1008490	GRIP! S , decorative ring, nickel
1008491	GRIP! S , decorative ring, gold

CRI	90
UGR ≤	25
Service life	50000 h
Risk Group	1
Length	12.4 cm
Width	10.1 cm
Height	8.4 cm
Net weight	0.256 kg
Gross weight	0.366 kg