


# GALEN PRO 60

**wall-mounted light, 3000 K, 20 W, DALI 2, touch, 54°, anthracite**

The GALEN PRO has a modern, functional design and its asymmetric light distribution makes it ideal for illuminating vertical surfaces - for example, wide area façade lighting or the illumination of advertising spaces and posters. The light is fitted with an IP68 rated 5-pin connector for safe and quick outdoor area installation. Available in two lengths (60 cm and 120 cm), both with DALI control, GALEN PRO offers great flexibility in the design and control of sophisticated outdoor lighting solutions for commercial or residential applications.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1009107 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 06 |
| **Impact resistance** | 1 Joule |
| **Assembly** | Surface |
| **Dimmable** | Yes |
| **Dimming technology** | DALI 2,Touch |
| **Number of through-wires** | 17 |
| **Primary nominal voltage** | 220-240V ~0/50/60 Hz |
| **Secondary power / voltage** | 305 mA |
| **Safety class** | I |
| **Wattage** | 20 W |
| **Minimum ambient temperature** | -25 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 17 |
| **Number of luminaires at LS C16A** | 28 |
| **Level of inrush current** | 31 A |
| **Duration of inrush current** | 262 µs |
| **Temperature at glass (light emission)** | 58 °C |
| **Lumen** | 2300 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 54 ° |

| | |
|---|---|
| 2432908 |  |

## Accessories

| | |
|---|---|
| 234354 | WALL MOUNTING BRACKET , for OUTDOOR BEAM and MILOX, silver, 80 cm |

| | |
|---|---|
| **Color** | anthracite |
| **CRI** | 80 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Width** | 60 cm |
| **Height** | 6.2 cm |
| **Depth** | 11.1 cm |
| **Net weight** | 1.69 kg |
| **Gross weight** | 2.1 kg |