
SIGHT PANEL

3~ spot, rectangular, 3000K, 38W, 70°, black

SIGHT PANEL - the high-output spot solution for 3-phase track mounting in shops, galleries or exhibition areas. With a 70° beam angle, CRI>90 and optional DALI control, it provides precise, high-quality light exactly where it is needed. The flexible swivel mechanism allows for precise alignment and the easy installation saves time - for perfect staging of any project.



TECHNICAL DATA

Item no.	1009146
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	210/260/310/380 mA
Safety class	I
Wattage	38 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	24
Number of luminaires at LS C16A	24
Level of inrush current	19 A
Duration of inrush current	280 µs
Lumen	6300 / 7700 / 9000 / 10800 lm
Colour temperature	3000 Kelvin
Beam angle	70 °
Color	black
CRI	90
UGR ≤	25
Service life	50000 h

Length	58 cm
Width	19 cm
Height	6.5 cm
Net weight	2.03 kg
Gross weight	2.39 kg