
BATTEN P 1200 52 830/840/850

BATTEN P 1200 52, 830/840/850 WH EM 3H

The BATTEN P is a rectangular surface-mounted wall and ceiling luminaire suitable for indoor use. It offers a light output ranging from 2,985 to 5,258 lumens and is designed for a service life of up to 100,000 hours. The housing is made of aluminium and measures 120 cm in length, 5.6 cm in width, and 6.5 cm in height. The luminaire features an IP20 protection rating and an impact resistance class of IK04, making it suitable for general indoor applications. It is equipped with an integrated emergency lighting function with a 3-hour runtime.



Light source

2432939	A to G: D

Accessories

1009262	BATTEN P SCK2000, 2000mm

Item no.	1009253
IP Code	IP20
Impact resistance class	IK04
Assembly	Surface
Assembly details	Ceiling,Wall,
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	20 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	28.0
Number of luminaires at LS C16A	47.0
Level of inrush current	17.7 A
Duration of inrush current	224 µs
Color	white
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	120 cm
Width	5.6 cm
Height	6.5 cm
Net weight	0.75 kg
Gross weight	0.8 kg