


NUMINOS® GIMBLE M | DL

NUMINOS® GIMBLE M, Recessed ceiling light, 4000 K, 20°, white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® GIMBLE M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Light source

2093752	A D

Item no.	1009587
Lamps included	No
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling,
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	20°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	9.5 cm
Diameter	13.5 cm
Net weight	0.41 kg
Gross weight	0.56 kg
Shape of cut-out	round
Installation depth	9,5 cm
Installation diameter	12 cm
BIG WHITE Page	43

Accessories

1010696	LED driver, 21W, 350 mA
1010700	LED driver, 20W, 350 mA, PHASE
1010704	LED driver, 23W, 350 mA, DALI
1010129	NUMINOS® M, reflector, gold
1010130	NUMINOS® M, reflector, copper
1010683	NUMINOS® M, Honeycomb diffuser
1010684	NUMINOS® M, Prismatic diffuser
1010685	NUMINOS® M, frosted diffuser
1010686	NUMINOS® M, Elliptical diffuser
1006143	Numinos® M Reducing ring, round 240/120 mm black
1006144	Numinos® M Reducing ring, round 240/120 mm white
1006145	Numinos® M Reducing ring, square 240/120 mm black
1006146	Numinos® M Reducing ring, square 240/120 mm white