
NUMINOS® M

Recessed ceiling light, 4000 K, 40°, IP20, round, black

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 12 watts, luminous flux of 1900 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009634
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1900 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.22 kg
Gross weight	0.28 kg

2093752	

Accessories

1010704	LED driver , 23W, 350 mA, DALI
1010700	LED driver , 20W, 350 mA, PHASE
1010129	NUMINOS® M , reflector, gold
1010683	NUMINOS® M , Honey-comb diffuser
1010686	NUMINOS® M , Elliptical diffuser
1010684	NUMINOS® M , Prisma-tic diffuser
1010696	LED driver , 21W, 350 mA
1010685	NUMINOS® M , frosted diffuser
1010130	NUMINOS® M , reflector, copper

Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	9 cm