
The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 12 watts, luminous flux of 1700 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1009660 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **IP Code** | IP20 |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 350 mA |
| **Safety class** | III |
| **Wattage** | 12 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 1700 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 20 ° |
| **Color** | white/chrome |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 8 cm |
| **Diameter** | 13.5 cm |
| **Net weight** | 0.35 kg |

| | |
|---|---|
| 2093870 |  |

## Accessories

| | |
|---|---|
| 1010704 | LED driver , 23W, 350 mA, DALI |
| 1010700 | LED driver , 20W, 350 mA, PHASE |
| 1010683 | NUMINOS® M , Honey-comb diffuser |
| 1010686 | NUMINOS® M , Elliptical diffuser |
| 1010684 | NUMINOS® M , Prisma-tic diffuser |
| 1010696 | LED driver , 21W, 350 mA |
| 1010685 | NUMINOS® M , frosted diffuser |
| 1010129 | NUMINOS® M , reflector, gold |
| 1010130 | NUMINOS® M , reflector, copper |

| | |
|---|---|
| **Gross weight** | 0.45 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 10 cm |
| **Installation diameter** | 12 cm |