
NUMINOS® MOVE M

Recessed ceiling light, 2700 K, 40°, IP20, round, white

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 12 watts, luminous flux of 1700 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1009662
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1700 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	8 cm
Diameter	13.5 cm
Net weight	0.35 kg

2093870	

Accessories

1010704	LED driver , 23W, 350 mA, DALI
1010700	LED driver , 20W, 350 mA, PHASE
1010129	NUMINOS® M , reflector, gold
1010683	NUMINOS® M , Honey-comb diffuser
1010686	NUMINOS® M , Elliptical diffuser
1010684	NUMINOS® M , Prisma-tic diffuser
1010696	LED driver , 21W, 350 mA
1010685	NUMINOS® M , frosted diffuser
1010130	NUMINOS® M , reflector, copper

Gross weight	0.45 kg
Shape of cut-out	round
Installation depth	10 cm
Installation diameter	12 cm