


NUMINOS® MOVE M | DL

NUMINOS® MOVE M, white/chrom recessed ceiling light 4000 K 20°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The diverse downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® MOVE DL M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 12 watts, luminous flux of 1900 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



Light source

2093752	A D

Item no.	1009696
Lamps included	No
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling,
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	20°
Color	white/chrome
CRI	90
UGR ≤	19
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	8 cm
Diameter	13.5 cm
Net weight	0.35 kg
Gross weight	0.45 kg
Shape of cut-out	round
Installation depth	10 cm
Installation diameter	12 cm

Accessories

1010696	LED driver, 21W, 350 mA
1010700	LED driver, 20W, 350 mA, PHASE
1010704	LED driver, 23W, 350 mA, DALI
1010129	NUMINOS® M, reflector, gold
1010130	NUMINOS® M, reflector, copper
1010683	NUMINOS® M, Honeycomb diffuser
1010684	NUMINOS® M, Prismatic diffuser
1010685	NUMINOS® M, frosted diffuser
1010686	NUMINOS® M, Elliptical diffuser
1006143	Numinos® M Reducing ring, round 240/120 mm black
1006144	Numinos® M Reducing ring, round 240/120 mm white
1006145	Numinos® M Reducing ring, square 240/120 mm black
1006146	Numinos® M Reducing ring, square 240/120 mm white