
The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009723
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2500 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black/chrome
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	11.5 cm
Diameter	16 cm
Net weight	0.606 kg

2093856	

Accessories

1010689	NUMINOS® L , Frosted diffuser
1010697	LED driver , 21W, 500 mA
1010687	NUMINOS® L , Honey-comb diffuser
1010701	LED driver , 19 W, 500 mA, PHASE
1010688	NUMINOS® L , Prismatic diffuser
1010690	NUMINOS® L , Elliptical diffuser
1010705	LED driver , 36W, 500 mA, DALI
1010132	NUMINOS® L , reflector, copper
1010131	NUMINOS® L , reflector, gold

Gross weight	0.756 kg
Shape of cut-out	round
Installation depth	11.5 cm
Installation diameter	14.5 cm