
Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 17 watts, a luminous flux of 2700 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1009806
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2700 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	white/chrome
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	8.5 cm
Diameter	13 cm
Net weight	0.434 kg
Gross weight	0.584 kg

2093752	

Accessories

1010689	NUMINOS® L , Frosted diffuser
1010697	LED driver , 21W, 500 mA
1010687	NUMINOS® L , Honey-comb diffuser
1010701	LED driver , 19 W, 500 mA, PHASE
1010688	NUMINOS® L , Prismatic diffuser
1010690	NUMINOS® L , Elliptical diffuser
1010705	LED driver , 36W, 500 mA, DALI
1010132	NUMINOS® L , reflector, copper
1010131	NUMINOS® L , reflector, gold

Shape of cut-out	round
Installation depth	8.5 cm
Installation diameter	12 cm