


NUMINOS® MOVE L | DL

NUMINOS® MOVE L, Recessed ceiling light, 2700 K, 40°, IP20, round, white

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. The various downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® MOVE DL L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 17 watts, luminous flux of 2400 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Light source

2093870	A G D

Item no.	1009823
Lamps included	No
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling,
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	40°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	9.3 cm
Diameter	16 cm
Net weight	0.51 kg
Gross weight	0.66 kg
Shape of cut-out	round
Installation depth	10,5 cm
Installation diameter	14.5 cm
BIG WHITE Page	35

Accessories

1010697	LED driver, 21W, 500 mA
1010701	LED driver, 19 W, 500 mA, PHASE
1010705	LED driver, 36W, 500 mA, DALI
1010131	NUMINOS® L, reflector, gold
1010132	NUMINOS® L, reflector, copper
1010687	NUMINOS® L, Honeycomb diffuser
1010688	NUMINOS® L, Prismatic diffuser
1010689	NUMINOS® L, Frosted diffuser
1010690	NUMINOS® L, Elliptical diffuser
1006147	Numinos® L Reducing ring, round 240/150 mm black
1006148	Numinos® L Reducing ring, round 240/150 mm white
1006149	Numinos® L Reducing ring, square 240/150 mm black
1006150	Numinos® L Reducing ring, square 240/150 mm white