


NUMINOS® MOVE L | DL

NUMINOS® MOVE L, black/chrome recessed ceiling light 4000 K 55°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® MOVE DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 17 watts, a luminous flux of 2700 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. This means that simple installation is a mere formality. When will you choose SLV's modular variety?



Light source

2093752	A D

Item no.	1009854
Lamps included	No
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling,
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	55°
Color	black/chrome
CRI	90
UGR ≤	22
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	9.3 cm
Diameter	16 cm
Net weight	0.51 kg
Gross weight	0.66 kg
Shape of cut-out	round
Installation depth	10,5 cm
Installation diameter	14.5 cm

Accessories

1010697	LED driver, 21W, 500 mA
1010701	LED driver, 19 W, 500 mA, PHASE
1010705	LED driver, 36W, 500 mA, DALI
1010131	NUMINOS® L, reflector, gold
1010132	NUMINOS® L, reflector, copper
1010687	NUMINOS® L, Honeycomb diffuser
1010688	NUMINOS® L, Prismatic diffuser
1010689	NUMINOS® L, Frosted diffuser
1010690	NUMINOS® L, Elliptical diffuser
1006147	Numinos® L Reducing ring, round 240/150 mm black
1006148	Numinos® L Reducing ring, round 240/150 mm white
1006149	Numinos® L Reducing ring, square 240/150 mm black
1006150	Numinos® L Reducing ring, square 240/150 mm white