
Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® GIMBLE XL recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1009884 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **IP Code** | IP20 |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 700 mA |
| **Safety class** | III |
| **Wattage** | 24 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 3600 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 20 ° |
| **Color** | black/chrome |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 13.5 cm |
| **Diameter** | 19 cm |
| **Net weight** | 0.8 kg |

| | |
|---|---|
| 2093861 |  |

## Accessories

| | |
|---|---|
| 1010698 | LED driver , 30W, 700 mA |
| 1010706 | LED driver , 36W, 700 mA, DALI |
| 1010694 | NUMINOS® XL , Elliptical diffuser |
| 1010692 | NUMINOS® XL , Prismatic diffuser |
| 1010702 | LED driver , 30W, 700 mA, PHASE |
| 1010693 | NUMINOS® XL , Frosted diffuser |
| 1010691 | NUMINOS® XL , Honeycomb diffuser |
| 1010133 | NUMINOS® XL , reflector, gold |
| 1010134 | NUMINOS® XL , reflector, copper |

| | |
|---|---|
| **Gross weight** | 1.05 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 13.5 cm |
| **Installation diameter** | 17.5 cm |