
NUMINOS® GIMBLE XL

Recessed ceiling light, 3000 K, 55°, white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. Like with the NUMINOS® GIMBLE XL recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009898
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	24 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3600 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	13.5 cm
Diameter	19 cm
Net weight	0.85 kg

2093861	

Accessories

1010698	LED driver , 30W, 700 mA
1010706	LED driver , 36W, 700 mA, DALI
1010694	NUMINOS® XL , Elliptical diffuser
1010133	NUMINOS® XL , reflector, gold
1010692	NUMINOS® XL , Prismatic diffuser
1010702	LED driver , 30W, 700 mA, PHASE
1010693	NUMINOS® XL , Frosted diffuser
1010134	NUMINOS® XL , reflector, copper
1010691	NUMINOS® XL , Honeycomb diffuser

Gross weight	1.1 kg
Shape of cut-out	round
Installation depth	13.5 cm
Installation diameter	17.5 cm