
Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you provide a thousand lighting design possibilities. Also with the NUMINOS® DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 24 watts, luminous flux of 3500 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1009935 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 700 mA |
| **Safety class** | III |
| **Wattage** | 24 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 3500 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 55 ° |
| **Color** | white/chrome |
| **CRI** | 90 |
| **UGR ≤** | 22 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 10.5 cm |
| **Diameter** | 16 cm |
| **Net weight** | 0.7 kg |
| **Gross weight** | 0.75 kg |

| | |
|---|---|
| 2093865 |  |

## Accessories

| | |
|---|---|
| 1010698 | LED driver , 30W, 700 mA |
| 1010706 | LED driver , 36W, 700 mA, DALI |
| 1010694 | NUMINOS® XL , Elliptical diffuser |
| 1010692 | NUMINOS® XL , Prismatic diffuser |
| 1010702 | LED driver , 30W, 700 mA, PHASE |
| 1010693 | NUMINOS® XL , Frosted diffuser |
| 1010691 | NUMINOS® XL , Honeycomb diffuser |
| 1010133 | NUMINOS® XL , reflector, gold |
| 1010134 | NUMINOS® XL , reflector, copper |

| | |
|---|---|
| **Shape of cut-out** | round |
| **Installation depth** | 10.5 cm |
| **Installation diameter** | 14.5 cm |