
NUMINOS® XL

Recessed ceiling light, 3000 K, 55°, IP20, round, black

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL XL recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 24 watts, a luminous flux of 3600 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1009942
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	24 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3600 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	10.5 cm
Diameter	16 cm
Net weight	0.704 kg
Gross weight	0.8 kg

2093861	

Accessories

1010698	LED driver , 30W, 700 mA
1010706	LED driver , 36W, 700 mA, DALI
1010694	NUMINOS® XL , Elliptical diffuser
1010133	NUMINOS® XL , reflector, gold
1010692	NUMINOS® XL , Prismatic diffuser
1010702	LED driver , 30W, 700 mA, PHASE
1010693	NUMINOS® XL , Frosted diffuser
1010134	NUMINOS® XL , reflector, copper
1010691	NUMINOS® XL , Honeycomb diffuser

Shape of cut-out	round
Installation depth	10.5 cm
Installation diameter	14.5 cm