
NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® MOVE DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 24 watts, a luminous flux of 3800 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1010025
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	24 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3800 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	white/chrome
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	11.6 cm
Diameter	19 cm
Net weight	0.58 kg

2093757	

Accessories

1010698	LED driver , 30W, 700 mA
1010706	LED driver , 36W, 700 mA, DALI
1010694	NUMINOS® XL , Elliptical diffuser
1010692	NUMINOS® XL , Prismatic diffuser
1010702	LED driver , 30W, 700 mA, PHASE
1010693	NUMINOS® XL , Frosted diffuser
1010691	NUMINOS® XL , Honeycomb diffuser
1010133	NUMINOS® XL , reflector, gold
1010134	NUMINOS® XL , reflector, copper

Gross weight	0.95 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	17.5 cm