
NUMINOS® GIMBLE XS

Recessed ceiling light, 3000 K, 20°, IP20, round, black

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1010044
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	950 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8 cm
Net weight	0.11 kg

2093745	

Accessories

1005614	NUMINOS® XS , frosted diffuser
1010126	NUMINOS® XS , reflector, copper
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1005612	NUMINOS® XS , diffuser
1010699	LED driver , 10W, 200 mA, PHASE
1005615	NUMINOS® XS , black diffuser
1010125	NUMINOS® XS , reflector, gold
1005613	NUMINOS® XS , transparent diffuser

Gross weight	0.21 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm