
FLATT II 62

Free-standing lamp, PHASE, 2700 K, IP65, square, black

The FLATT II light range combines modern design with high functionality. The wall-mounted and bollard lights are ideal for accentuated façade and path lighting. With a sea air resistant coating, dark sky compliant light distribution (ULOR <2%), 2,700K warm white light and optional sensor technology, they offer flexible solutions for residential and HoReCa applications.



TECHNICAL DATA

Item no.	1010106
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Ground
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Number of through-wires	200
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	210
Number of luminaires at LS C16A	210
Level of inrush current	4.1 A
Duration of inrush current	81 µs
Temperature at glass (light emission)	75 °C
Lumen	650 lm

Accessories

228726	Y-CONNECTION BOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68

Colour temperature	2700 Kelvin
Color	black
CRI	80
Service life	50000 h
Risk Group	1
Length	18 cm
Width	6 cm
Height	62 cm
Net weight	2.11 kg
Gross weight	2.51 kg