


# THEO PRO S

**Wall-mounted light, single, DALI, P2, rectangular, 2700 K, 6W, 24°, white**

The THEO PRO wall light series combines a clear, square design with modern technology for precise accent lighting. Available in two sizes and performance classes, with single or up/down light, they offer versatile solutions for modern façade lighting in outdoor areas thanks to DALI control and resistance to sea air.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010182 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 06 |
| **Impact resistance** | 1 Joule |
| **Assembly** | Surface |
| **Assembly details** | Wall |
| **Dimmable** | Yes |
| **Dimming technology** | DALI |
| **Number of through-wires** | 15 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 150 mA |
| **Safety class** | I |
| **Wattage** | 6 W |
| **Minimum ambient temperature** | -25 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 15 |
| **Number of luminaires at LS C16A** | 24 |
| **Level of inrush current** | 65 A |
| **Duration of inrush current** | 200 µs |
| **Temperature at glass (light emission)** | 56 °C |
| **Lumen** | 600 lm |

| | |
|---|---|
| 1028936 |  |

## Accessories

| | |
|---|---|
| 1010939 | |

| | |
|---|---|
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 24 ° |
| **Color** | white |
| **CRI** | 80 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Width** | 6.5 cm |
| **Height** | 17.5 cm |
| **Depth** | 10 cm |
| **Net weight** | 0.82 kg |
| **Gross weight** | 1.03 kg |
| **BIG WHITE Page** | 869 |