

# THEO PRO L

**Wall-mounted light, single, DALI, P1, rectangular, 2700 K, 10W, 24°, white**

The THEO PRO wall light series combines a clear, square design with modern technology for precise accent lighting. Available in two sizes and performance classes, with single or up/down light, they offer versatile solutions for modern façade lighting in outdoor areas thanks to DALI control and resistance to sea air.

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010186 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 08 |
| **Impact resistance** | 5 Joule |
| **Assembly** | Surface |
| **Assembly details** | Wall |
| **Dimmable** | Yes |
| **Dimming technology** | DALI 2 |
| **Number of through-wires** | 15 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 250 mA |
| **Safety class** | I |
| **Wattage** | 10 W |
| **Ambient temperature** | 80 °C |
| **Minimum ambient temperature** | -25 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 15 |
| **Number of luminaires at LS C16A** | 24 |
| **Level of inrush current** | 65 A |
| **Duration of inrush current** | 200 µs |
| **Lumen** | 1200 lm |

| | |
|---|---|
| |  |

| | |
|---|---|
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 24 ° |
| **Color** | white |
| **CRI** | 80 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Width** | 10.8 cm |
| **Height** | 30.5 cm |
| **Depth** | 15.5 cm |
| **Net weight** | 1.82 kg |
| **Gross weight** | 2.4 kg |