

# QUAD PRO 60

**Free-standing lamp, DALI, 2700 K, IP65, rectangular, anthracite**

The QUAD PRO bollard lights combine timeless design with high robustness (IK10) and a special sea air-resistant coating. The asymmetrical optics enable optimum, standard-compliant illumination of pathways. With a ULOR-<1%, the lights comply with nature conservation requirements to prevent light pollution. Available in two heights (600 mm / 900 mm) and two light colours (2,200 K and 2,700 K), for flexible lighting concepts in outdoor areas.

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010205 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 10 |
| **Impact resistance** | 20 Joule |
| **Assembly** | Surface |
| **Assembly details** | Ground |
| **Dimmable** | Yes |
| **Dimming technology** | DALI |
| **Number of through-wires** | 120 |
| **Primary nominal voltage** | 100-240V ~50/60 Hz |
| **Secondary power / voltage** | 500 mA |
| **Safety class** | I |
| **Wattage** | 14 W |
| **Minimum ambient temperature** | -25 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 170 |
| **Number of luminaires at LS C16A** | 170 |
| **Level of inrush current** | 8.6 A |
| **Duration of inrush current** | 135 µs |
| **Temperature at glass (light emission)** | 60 °C |
| **Lumen** | 500 lm |

| | |
|---|---|
| |  |
| |  |

| | |
|---|---|
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 45 ° |
| **Color** | anthracite |
| **CRI** | 80 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Width** | 8 cm |
| **Height** | 60 cm |
| **Depth** | 16 cm |
| **Net weight** | 3.02 kg |
| **Gross weight** | 4 kg |