


DYSKO | CW, SINGLE, PHASE

DYSKO, CW, SINGLE, PHASE, Wall and ceiling surface-mounted luminaire, 2700 K, 6.7 W, 36°, black

The DYSKO wall and ceiling surface-mounted luminaire is designed for installation on walls and ceilings in indoor areas. It features a colour temperature of 2700 K and produces a luminous flux of 750 lumens at a power consumption of 6.7 watts. The luminaire has a beam angle of 36° and is equipped with phase-cut dimming, allowing for stepless brightness adjustment. The housing is made of aluminium and measures 15.3 cm in length, 5.4 cm in width, and 6.8 cm in height. The IP20 rating makes it suitable for use in dry indoor environments, while the IK02 classification provides low impact resistance. The luminaire has a lifespan of 50,000 hours.



Light source

2093820	A G D

Item no.	1010302
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	150 mA
Safety class	I
Wattage	7 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	97.0
Number of luminaires at LS C16A	121.0
Level of inrush current	15 A
Duration of inrush current	30 µs
Beam angle	36°
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	15.3 cm
Width	5.4 cm
Height	6.8 cm