


DYSKO | 1PH., PD, PHASE

DYSKO, 1~ Pendant luminaire, PHASE, 2700 K, 6.7 W, 36°, black

The DYSKO 1~ pendant luminaire is designed for ceiling mounting indoors and is particularly suitable for use in residential and work areas. It provides a luminous flux of 750 lumens with a colour temperature of 2700 Kelvin and a beam angle of 36°, allowing for targeted and pleasant lighting. The luminaire features phase-cut dimming, enabling stepless adjustment of the light intensity. The housing is made of aluminium and polycarbonate. The luminaire has a diameter of 5.4 cm, a height of 4.8 cm, and a pendant length of 200 cm. The IP20 protection rating and IK02 impact resistance ensure safe operation indoors. Installation is carried out as a track system pendant, offering flexible mounting options.



Light source

2093820	A to G: D

Item no.	1010326
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Track
Assembly details	Pendant mounted,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	150 mA
Safety class	II
Wattage	7 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	50.0
Number of luminaires at LS C16A	80.0
Level of inrush current	10 A
Duration of inrush current	16 µs
Beam angle	36°
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	4.8 cm
Diameter	5.4 cm
Pendant length	200.0000 cm