# PANEL 60

**Ceiling-mounted light, round, DALI, 3000/4000K, 29W, 90°, grey**

The new PANEL 60 - the efficient lighting solution for office and general areas. With a switchable colour temperature (3,000/4,000 K), CRI>90, improved energy efficiency and UGR<19, it meets all the requirements of modern workplaces. Ideal as a replacement for existing systems: simply replace and benefit immediately!

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010425 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Surface |
| **Assembly details** | Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | DALI,Touch |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 750 mA |
| **Safety class** | I |
| **Wattage** | 29 W |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 29 |
| **Number of luminaires at LS C16A** | 48 |
| **Level of inrush current** | 14.75 A |
| **Duration of inrush current** | 256 µs |
| **Lumen** | 3050 / 3300 lm |
| **Colour temperature** | 3000/4000 Kelvin |
| **Beam angle** | 90 ° |
| **Color** | gray |

| | |
|---|---|
| |  |

| | |
|---|---|
| CRI | 90 |
| UGR ≤ | 19 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 6 cm |
| Diameter | 60 cm |
| Net weight | 4.8 kg |
| Gross weight | 6.2 kg |
| Shape of cut-out | round |
| Installation depth | 7 cm |
| Installation diameter | 20 cm |