
# GLENOS® PRO

**pendant light, 1.2m, DALI, UGR16, pendant length 210 cm, 3000K, 75°, black**

GLENOS® PRO is the new linear light range from SLV for sophisticated office and contract lighting. Whether pendant, surface mounted or recessed, all lights are glare-free (UGR<16/19) thanks to the micro-reflector and offer high efficiency of up to 134 lm/W with CRI>90. The lights can be connected seamlessly without light spillage, are halogen-free and guarantee uniform illumination with high visual comfort.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010510 |
| **Number of different light outlets** | 2 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Surface |
| **Dimmable** | Yes |
| **Dimming technology** | DALI,Touch |
| **Number of through-wires** | 15 |
| **Primary nominal voltage** | 220-240V ~0/50/60 Hz |
| **Secondary power / voltage** | 1600 mA |
| **Safety class** | I |
| **Wattage** | 60 W |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 10 |
| **Number of luminaires at LS C16A** | 17 |
| **Level of inrush current** | 30 A |
| **Duration of inrush current** | 346 µs |
| **Lumen** | 6900 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 75 ° |
| **Color** | black |

| | |
|---|---|
| |  |
| |  |

| | |
|---|---|
| **CRI** | 90 |
| **UGR ≤** | 16 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 128.5 cm |
| **Width** | 4.8 cm |
| **Height** | 7.6 cm |
| **Pendant length** | 210 cm |
| **Net weight** | 3.5 kg |
| **Gross weight** | 5.2 kg |