


# DOWNLIGHT P

**115 18 HG 840 60 ML DALI WH IP54**

The DOWNLIGHT P combines a robust design with high efficiency: up to 170 lm/W, 80,000 h service life (L80B10) and multi-lumen function make it the ideal choice for offices, corridors or common areas. With a UGR value of 21 or 23, it provides pleasant light - available in versions with DALI control or as an on/off version.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010759 |
| **IP Code** | IP54 |
| **Impact resistance class** | IK 08 |
| **Dimmable** | Yes |
| **Dimming technology** | DALI |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 100-700 mA |
| **Safety class** | II |
| **Wattage** | 5 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 36 |
| **Number of luminaires at LS C16A** | 60 |
| **Level of inrush current** | 21 A |
| **Duration of inrush current** | 180 µs |
| **Lumen** | 600 / 4250 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 60 ° |
| **Color** | white |
| **CRI** | 80 |
| **Binning** | 3 SDCM |
| **Service life** | 50000 h |

| | |
|---|---|
| 2194011 |  |

| | |
|---|---|
| **Depth** | 6.9 cm |
| **Diameter** | 11.5 cm |
| **Net weight** | 0.52 kg |
| **Gross weight** | 0.6 kg |
| **Shape of cut-out** | round |
| **Installation diameter** | 10 cm |