


WATERPROOF C

1500 71 830/840/850 ML DALI IP66

The WATERPROOF moisture-proof luminaire offers energy-efficient lighting solutions in three performance classes, with up to 180 lm/W, IP66, IK08 and a service life of up to 100,000 hours. Thanks to tool-free cap opening and integrated through-wiring, installation is particularly quick. Optionally with DALI and sensor - ideal for industry, warehouses or underground car parks.



TECHNICAL DATA

Item no.	1010819
IP Code	IP65
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	200-350 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	24
Number of luminaires at LS C16A	33
Level of inrush current	29 A
Duration of inrush current	236 µs
Lumen	4105 / 7687 lm
Colour temperature	3000/4000/5000 Kelvin
Beam angle	120 °
Color	gray
UGR ≤	27

Service life	75000 h
Risk Group	1
Length	150 cm
Width	8 cm
Height	7.4 cm
Net weight	1.84 kg
Gross weight	2.06 kg