


WATERPROOF P 1500 81 830/840/850 | 81 830/840/850 ML IP65

WATERPROOF P, 1500 81 830/840/850 ML IP66

The WATERPROOF P is a rectangular-shaped damp room luminaire suitable for wall and ceiling mounting in demanding environments. It features a housing made of PC and steel, ensuring an IP66 protection rating and IK08 impact resistance. With a length of 150 cm, a width of 8 cm, and a height of 7.4 cm, it offers a robust and compact design. The luminaire is designed for use in areas requiring high protection against the ingress of dust and water. It provides a long-lasting lighting solution with a service life of up to 100,000 hours.



Light source

2481888	A C G

Item no.	1010825
IP Code	IP66
Impact resistance class	IK08
Assembly	Surface
Assembly details	Ceiling,Wall,
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	18.0
Number of luminaires at LS C16A	31.0
Level of inrush current	33.1 A
Duration of inrush current	168 µs
Beam angle	120°
Color	gray
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	150 cm
Width	8 cm
Height	7.4 cm
Net weight	1.76 kg
Gross weight	1.98 kg