


WATERPROOF P 1500 81 830/840/850 | 81 830/840/850 ML DALI IP65

WATERPROOF P, 1500 81 830/840/850 ML DALI IP66

The WATERPROOF P is a moisture-resistant luminaire in a rectangular design, intended for wall and ceiling mounting. It is especially suitable for use in demanding environments with high humidity levels. The housing is made of plastic and steel, providing protection rated at IP66 and impact resistance of class IK08. The luminaire features DALI-2 dimming and has a declared service life of 100,000 hours. With a length of 150 cm, a width of 8 cm, and a height of 7.4 cm, it is compactly designed and allows for flexible installation. The light output is available in various colour temperatures (830/840/850) and offers a reliable lighting solution for professional applications.



Light source

2481888	A C

Item no.	1010831
IP Code	IP66
Impact resistance class	IK08
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	DALI
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	24.0
Number of luminaires at LS C16A	33.0
Level of inrush current	29 A
Duration of inrush current	236 µs
Beam angle	120°
Color	gray
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	150 cm
Width	8 cm
Height	7.4 cm
Net weight	1.84 kg
Gross weight	2.06 kg